BARCODE YES

Star
Mid Range CCD

STAR is a high performance mid range CCD designed to satisfy all the applications that need to read a barcode.

Excellent scanning rate by means of the fast 32 bit CPU which allows to reach a depth of field up to 5 cm.

On board Keyboard Wedge and USB Interfaces RS232 (optional) that can be obtained by replacing the cable with ease.

Powerful Data Editing help truncations and preambles postambles.

A sturdy ergonomic and very competitive scanner.

USB B
UNIVERSAL SERIAL BUS

www.barcodeyes.com

Mid Range Scanner

USB

Linear Imaging optic
No Contact CCD

Specifications

Physical Characteristics

Depth: 20 mm
Width: 80 mm
Height: 160 mm
Weight: 90 g.

Electrical

Input: 5 V. DC
Power: 110 mAh max.

Interfaces

USB, RS232 (opz.)

Scanner Characteristics

Light Source: Led Diode 635 nm.
Depth of Field: 0 to 50 mm.
Scan Rate: 200 Scan/Sec
Resolution: 4 mil
Contrast: 30% @ UPC / EAN 100%

Symbologies

UPC/EAN/JAN, UPC/EAN/JAN Add on, Code 39 standard, Code 39 Full ASCII, Codabar, Interleaved 2/5 Code 128,Code 93, Standard 2/5, Code 11, MSI, Code 32 EAN-128, ISBN, Italian Pharma code 32

Operational

cable: 180 Cm. straight cable
Connector: RJ45 to USB / DSUB / PS2
Reading Indicator: Led, buzzer

Environmental

Operating Temp: 0° to 50°
Storage temp: -20° to 70°
Humidity: 20% to 95% RH (non condensing)

European manufacturing and distribution of AUTO ID devices

CE   RoHS LEAD FREE